

BESKRIVNING

Total tjocklek	EN 428	mm	4.60
Slitskikt tjocklek	EN 429	mm	0.70
Vikt	EN 430	g/m ²	5595
Plattstorlek	EN 427	mm	500.5 x 500.5
Antal plattor / palket	-	-	10





KLASSIFICERING

Norm / Produktspecifikation	-	-	EN 652
Europaklass	EN 685	klass	34 - 42
Brandklassificering	EN 13 501-1	klass	B _{fl} -s1
Elektrisk uppladdning	EN 1815	kV	< 2
Friktion, våt : ramptest med olja	DIN 5130	klass	R10

TESTVÄRDEN

Slitagemotstånd	EN 660.2	mm ³	≤ 2.0
Slitklass	EN 652	-	T
Dimensionsstabilitet	EN 434	%	≤ 0.15
Intryckskänslighet	EN 433	mm	0.18
Ljudisolering	EN ISO 717-2	dB	15
Värmemotstånd	EN 12524	W/(m.K)	0.25
Färgbeständighet	EN 20 105 - B02	degree	≥ 6
Kemikaliebeständighet	EN 423	-	OK
Ytbehandling	-	-	Protecsol®

CE-MÄRKNING

	EN 14041	-	  
		-	