

MIPOLAM SYMBIOZ™

MIPOLAM SYMBIOZ™ is a fully flexible homogeneous compacted floorcovering in sheet, 2m wide, abrasion group T, providing excellent resistance to wear and tear in high traffic areas. Its weight is 2580 gr/m².

It features a non directional design incorporating coloured chips to ensure an even colour throughout the thickness.

MIPOLAM SYMBIOZ™ contains over 75% sustainable or renewable raw materials. It includes a 100% bio based plasticizer, made of residues from cereals (wheat, corn...).

This floorcovering has extremely low VOC emissions, more than 40 times lower than the European standards.

In addition, the floorcovering features Evercare™, new patented surface treatment, providing unrivalled level of maintenance and chemical resistance.

Evercare™ is a Polyurethane treatment micro structured, cross coat polymerised, using laser technology and is acting as a barrier against stains and chemical aggression. It definitively replaces the application of wax or polish during the life time of the product.

As part of our sustainable development policy, this product is manufactured in the first floor covering plant awarded with the triple certification: ISO 9001 (quality), ISO 14 001 (environment) and OHSAS 18001 (safety).

		Mipolam Symbioz™	
DESCRIPTION / BESCHREIBUNG / DESCRIPTION / BESCHRIJVING / DESCRIPCIÓN / DESCRIÇÃO / DESCRIZIONE			
Total thickness / Gesamtdicke / Epaisseur totale / Totale dikte / Espesura total / Spessore totale	EN 428	mm	2
Weight / Flächengewicht / Poids / Gewicht / Peso / Peso / Peso	EN 430	g/m ²	2580
Width/length of sheet / Bahnenbreite/-länge / Largeur/longueur des lés / Rolbreedte/Rollenlengte / Ancho/largo de rollos / Largura/comprimento dos rollos / Larghezza/lunghezza dei teli	EN 426	cm/lm	200/20
CLASSIFICATION / KLASSIFIZIERUNG / CLASSIFICATION / CLASSIFICATIE / CLASIFICACIONES / CLASSIFICAÇÕES / CLASSIFICAZIONI			
Norm/product specification / Produkt Norm / Norme produit / Technische eigenschappen / Normas / Normas / Norma prodotto	-	-	EN 649
European classification / Europäische Klassifizierung / Classement européen / Europese classificatie / Europea / Europa / Europa	EN 685	class	34-43
K rating / Beanspruchungsklasse / Classement K / K classificatie / Clasificación K / Classificação K / Classificazione K	-	class	K5
Fire rating / Brandverhalten / Classement feu / Brand classificatie / Fuego / Fogo / Reazione al fuoco	EN 13501-1	class	Br1 - s1
Static electrical propensity / Begehaufatdung / Potentiel de charge / Elektrische eigenschappen / Compartimento electrostático / Compartimento electrostático / Resistenza elettrica	EN 1815	kV	< 2
Slip resistance wet / Rutschhemmung / Glissance humide / Anti-slip / Deslizamiento húmedo / Escorregamento húmido / Scivolosità umida	DIN 51130	class	R9
Slip resistance / Rutschhemmung / Glissance / Anti-slip / Deslizamiento / Escorregamento / Scivolosità	NF EN 13893	-	≥ 0.30 (DS)
PERFORMANCES / TECHNISCHE EIGENSCHAFTEN / PERFORMANCE / TESTRESULTAAT / CUALIDADES TÉCNICAS / PERFORMANCE / CARATTERISTICHE TECNICHE			
Wear resistance / Verschleißverhalten / Résistance à l'usure / Slijtvastheid / Abrasión / Abrasão / Resistenza all'abrasione	EN 660.2	mm ³	≤ 2.0
Wear group / Verschleißgruppe / Groupe d'abrasion / Groep slijtvastheid / Grupo de abrasión / Grupo de abrasão / Gruppo di abrasione	EN 649	group	T
Dimensional stability / Maßstabilität / Stabilité dimensionnelle / Maatvastheid / Estabilidad dimensional / Estabilidade dimensional / Stabilità dimensionale	EN 434	%	≤ 0.40
Residual indentation / Resteindruck / Poinçonnement statique rémanent / Indrukbelasting / Punzonamiento / Punçoamento / Impronta	EN 433	mm	≈ 0.03
Thermal conductivity / Wärmeleitfähigkeit / Conductivité thermique / Thermische weerstand / Resistencia térmica / Resistência térmica / Resistenza termica	EN 12 524	W/(m.K)	0.25
Colour fastness / Lichtechtheit / Solidité lumière / Lichtecheitheid / Resistencia a la luz / Estabilidade das cores / Solidità alla luce	EN 20 105 - B02	degree	≥ 6
Chemical resistance / Verhalten gegenüber Chemikalien / Résistance aux produits chimiques / Chemische beständigheid / Resistencia a los productos químicos / Resistência aos produtos químicos / Resistenza ai prodotti chimici	EN 423	class	OK
Bacteriostatic and fungistatic treatment / Fungistatisch und bakteristatisch / Fongistatique et bactériostatique / Bacteriologisch en schimmelwerend / Bacteriostático e fungistático / Bacteriostático e fungistático / Batteriostatico e micostatico	DIN EN ISO 846-A/C	-	no growth ständig gegenüber nicht färbenden alkoholhaltiger Handsprinklerlösungen, Haushaltschemikalien und verdünnten Säuren und Laugen bei kurzzeitiger Einwirkung.
Surface treatment / Oberflächenvergrütung / Traitement de surface / Oppervaktebehandling / Tratamiento de superficie / Tratamento de superficie / Tratamento de superficie	Polyurethane patented treatment	-	EVERCARE™
CE MARKING / CE KENNZEICHNUNG / MARQUAGE CE / EG-CONFORMITEITSMERK / MARCA DE CONFORMIDAD CE / MARCA DE CONFORMIDADE CE / MARCATURA CE DI CONFORMITA			
CE	EN 14041	-	



UK reference - January 2011

INSTALLATION

- Highly flexible homogeneous flooring
- Easy to install & weld

The lowest environmental impact at every stage of the product life

TRANSPORT

- Product weight 20% lower than standard product
- All raw materials available within 350 km from production site

PRODUCTION

- Made in Germany
- ISO9001, ISO14001 and OHSAS 18001 certified factory
- 100% post manufacturing wastes recycled

ASIA: Gerflor Asia
Tel: +852 9222 6355 - Fax: +852 3006 1449
e-mail: gerflorasia@gerflor.com

AUSTRALIA/NEW ZEALAND: Gerflor Australasia Pty. Ltd
Australia Tel: 1 800 060 785 - New Zealand Tel: 0 800 630 111
e-mail: gerflor@gerflor.com.au

AUSTRIA/SWITZERLAND: Gerflor GmbH
Tel: +43 (0)7229/70800-0 - Fax: +43 (0)7229/70800-218
e-mail: austria@gerflor.com - switzerland@gerflor.com

BELGIUM/LUXEMBURG: Gerflor Benelux
Tel: +32 (0)3 766 42 82 - Fax: +32 (0)3 766 29 14
e-mail: gerflorbelgium@gerflor.com

CANADA: Gerflor International
Tel: +1 450 538 9828 - Fax: +1 450 538 9827
e-mail: gerflorcanada@gerflor.com

CHINA: Gerflor China
Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998
e-mail: gerflorchina@gerflor.com

FINLAND: Gerflor OY
Tel: +358 (0) 10 617 5150 - Fax: +358 (0) 10 617 5152
e-mail: info@gerflor.fi

FRANCE: Gerflor - Service Express:

GERMANY: 0 810 569 569 (Germany) 0 810 569 570 (Germany)
e-mail: contact@gerflor.com

GERMANY: Gerflor Mipolam GmbH
Tel: 0 22 41-25 30-0
e-mail: GerflorMipolam@gerflor.com

Kunden-Service: kundenservice@gerflor.com
Tel: 0 22 41-25 30-131 - Fax: 0 22 41-25 30-100
SAT Service und Anwendungstechnik: Technik@gerflor.com
Tel: 0 22 41-25 30-555 - Fax: 0 22 41-25 30-550

IRELAND: Gerflor Ltd
Tel: +353 (0) 42 96 61431 - Fax: +353 (0) 42 96 61759
e-mail: gerflorir@gerflor.com

ITALY: Gerflor S.p.A.
Tel: +39 02 90 78 60 12 r.a. - Fax: +39 02 90 42 74 84
e-mail: gerflorit@gerflor.com

LATIN AMERICA (Brazil): Gerflor América Latina
Tel: +55 11 38 48 20 20 - Fax: +55 11 38 48 20 23
e-mail: gerflor@gerflor.com.br

MIDDLE EAST: Gerflor Middle East
Tel: +966 3 847 1779 - Fax: +966 3 847 1781
e-mail: gerflorME@gerflor.com

NETHERLANDS: Gerflor BV
Tel: +31 (0)40 266 17 00 - Fax: +31 (0)40 257 46 89
e-mail: gerflorNL@gerflor.com

OTHER COUNTRIES: Gerflor International
Tel: +33 (0)4 74 05 40 00 - Fax: +33 (0)4 74 05 03 13
e-mail: gerflorcontract@gerflor.com

POLAND: Gerflor Polska Sp z o.o
Tel: + 48 61 823 34 01 - Fax: + 48 61 823 34 33
e-mail: info@gerflor.pl

PORTUGAL: Gerflor Iberia, SA
Tel: +351 21 843 95 49 - Fax: +351 21 846 55 44
e-mail: gerflorportugal@gerflor.com

RUSSIA: Gerflor Moscow Office
Tel: + 7 495 430-86-54 / 65 - Fax: + 7 495 430-85-46
e-mail: gerflorruss@mspk.east.ru

SCANDINAVIA: Gerflor Scandinavia a.s.
Tel: + 47 64 95 60 70 - Fax: + 47 64 95 60 80
e-mail: gerflorscand@gerflor.no

SPAIN: Gerflor Iberia, SA
Tel: +34 91 653 50 11 - Fax: +34 91 653 25 85
e-mail: gerfloriberia@gerflor.com

UNITED KINGDOM: Gerflor Ltd
Tel: + 44 (0) 1926 622 600 - Fax: + 44 (0) 1926 401 647
e-mail: contractuk@gerflor.com

USA: Gerflor North America
Tel: 877 GERFLOR (437 3567) - Fax: 847 394 3753
e-mail: info@gerflorusa.com



Committed to sustainable development

gerflor.com

ARCHITECTURE
DECORATION
SPORT
TECHNOSPECIFIC

Gerflor
theflooringgroup

MIPOLAM SYMBIOZ™

gerflor.com



Gerflor
theflooringgroup



Mipolam Symbioz™

the next generation floor

Life

- Highest durability : T group
- Very low VOC Emission
- 100% recyclable



Revolutionary patented surface treatment
No wax for life
Highest stain resistance



RAW MATERIALS

- 75% sustainable or renewable resources
- 100% bio based plasticizer

Credit: mairbrown - Edition: Götterberg News - 5/2011 - 01/2011

MIPOLAM SYMBIOZ™

 T EVERCARE™  100% recyclable



6027 Acacia WR: 0000



6007 Garden WR: 0000



6006 Blue Sky WR: 0000



6017 Grass WR: 0000



6016 Sea Blue WR: 0000



6037 Lagoon WR: 0000




6046 Blue Night WR: 0000

WR: Welding Rods - Reference number: 0507 + [WR] code

MIPOLAM SYMBIOZ™

 T EVERCARE™  100% recyclable



6048 Lavender WR: 0000



6055 Tomato WR: 0000



6035 Sunset WR: 0000



6032 Sunshine WR: 0000


WR: Welding Rods - Reference number: 0507 + [WR] code

MIPOLAM SYMBIOZ™

 T EVERCARE™  100% recyclable




6059 Black Diamond WR: 0000



6044 Sea Storm WR: 0000



6039 Pebble WR: 0000



6032 Sunshine WR: 0000

WR: Welding Rods - Reference number: 0507 + [WR] code

MIPOLAM SYMBIOZ™


 T EVERCARE™  100% recyclable




6029 Cloud WR: 0000



6010 Mist WR: 0000



6009 Grey Stone WR: 0000




6008 Calico WR: 0000

WR: Welding Rods - Reference number: 0507 + [WR] code

MIPOLAM SYMBIOZ™

 T EVERCARE™  100% recyclable



6045 Chocolate WR: 0000



6034 Mole WR: 0000



6043 Wood WR: 0000



6004 Sandstone WR: 0000



6041 Clay WR: 0000



6003 Linen WR: 0000



6031 Breeze WR: 0000



6001 Cotton WR: 0000

WR: Welding Rods - Reference number: 0507 + [WR] code