





|   | PRODUCT CHARACTERISTICS    |             |                   |  |
|---|----------------------------|-------------|-------------------|--|
|   | Standard                   | Requirement | Unit              | Results  |
|   | PRODUCT DESCRIPTION        |             |                   |  |
| Surface treatment   | -                          | -           | -                 | Pur Protect  |
| Surface complex   | -                          | -           | -                 | Wear layer 100% pur PVC  |
| Foam  | -                          | -           | -                 | Closed cell foam   |
| Thickness   | EN ISO 24346               | -           | mm                | <b>6 mm</b><br> |
| Weight  | EN ISO 23997               | -           | kg/m <sup>2</sup> | 3.7  |
| Length  | EN ISO 24341               | -           | lm                | 20.5 Standard  |
| Width   | EN ISO 24341               | -           | lm                | 1.5  |
|   | SPORT PROPERTIES           |             |                   |  |
| Shock absorption  | EN 14808                   | ≥ 25        | %                 | <br>P1          |
| Vertical deformation  | EN 14809                   | ≤ 3.5       | mm                | ≤ 2 (P1)   |
| Sliding coefficient   | EN 13036-4                 | 80 to 110   | -                 | 80 - 110   |
| Ball bounce   | EN 12235                   | ≥ 90        | %                 | ≥ 90   |
|   | TECHNICAL CHARACTERISTICS  |             |                   |  |
| Abrasion resistance   | EN ISO 5470-1              | ≤ 1000      | mg                | ≤ 350  |
| Impact resistance   | EN 1517                    | ≥ 8         | N/m               | ≥ 8  |
| Indentation resistance  | EN 1516                    | ≤ 0.5       | mm                | ≤ 0.5  |
| Impact sound insulation   | EN ISO 717-2               | -           | dB                | 18   |
|   | CLASSIFICATION             |             |                   |  |
| Fire  | EN 13501-1                 | -           | -                 | <br>Cfl-s1    |
| Anti-bacterial activity<br>(E. coli - S. aureus - MRSA)*                            | ISO 22196                  | -           | -                 | > 99 % inhibits growth   |
|   | DECLARATION OF PERFORMANCE |             |                   |  |
|  | DOP-005-1007-A             | -           | -                 | Fire<br>Sliding Coefficient<br>Abrasion Resistance<br>Rolling Load Resistance                      |

\* The implementation of an effective cleaning method is the best defence against infection